

## **CYCLE 2025-07**

Sorting order:

A – first 'quotas', then 'suspensions'

B – **new** requests, **amending** requests.

>>>The duty suspension and quota requests on the following list are currently under discussion. The data available on this list may not represent the final state of the discussions within the relevant Commission Working group.

Please note that it cannot be guaranteed that the information available exactly reproduces an officially adopted text. Only European Union legislation published in the Official Journal of the European Union is deemed authentic<<<

CN code	TARIC	Reference Mail	Working Number	Description	<u>Quotas</u>	New or amendment request	Measure status	Partner Position Country	Partner Position	Public Comments
2912 29 00		6299867/2024	1001	Cyclohex-3-en-1-carbaldehyde (CAS RN 100-50-5) with a purity of 98 % or more	Q/77tonnes, 01.07-31.12	New	UNDER EXAMINATION			
2917 39 85		6560149/2024	3312	1,3-dioxo-1,3-dihydro-2-benzofuran-5-carboxylic acid (CAS RN 552-30-7) with a purity by weight of 97 % or more	Q/4300tonnes, 01.07-31.12	New	UNDER EXAMINATION			
2918 11 00		6469278/2024	1015	L-(+)-lactic acid (CAS RN 79-33-4) with a purity by weight of 99 % or more	Q/56000tonnes, 01.07-31.12	New	UNDER EXAMINATION			
2932 19 00		6819955/2024	3356	Tetrahydro-2-methylfuran (CAS RN 96-47-9) with a purity by weight of 99 % or more	Q/2000000kilo grams, 01.07-31.12	New	UNDER EXAMINATION			
2933 59 95		6546261/2024	3303	Ametoctradin (CAS RN 865318-97-4) with a purity by weight of 98 % or more	Q/353500kilograms, 01.07-31.12	New	UNDER EXAMINATION			

2933 99 80		6469451/2024	1016	L-Tryptophan (CAS RN 73-22-3) with a purity by weight of 98,5 % or more	Q/6000kilograms, 01.07-31.12	New	UNDER EXAMINATION			
3815 19 90		6412686/2024	1013	Catalyst consisting of organo-metallic compounds of boron and titanium, fixed on a support of silicon dioxide, in the form of powder	Q/7800kilograms, 01.07-31.12	New	UNDER EXAMINATION			
3907 29 20		7015592/2024	1044	Polyether polyol with a total bio content of 35 % and containing by weight <ul style="list-style-type: none"> <li>- 9 % or more but not more than 15 % of palm oil,</li> <li>- 20 % or more but not more than 25 % of sucrose</li> <li>- with a hydroxyl number of 420 or more but not more than 460 and a viscosity index of 3 000 or more but not more than 4 000</li> </ul>	Q/1000000kilograms, 01.07-31.12	New	UNDER EXAMINATION			
8409 91 00		6838521/2024	1042	Cylinder head blank for a four cylinder engine with 10 cores, made of aluminium alloy EN AC-45500, with: <ul style="list-style-type: none"> <li>- no other components,</li> <li>- a hardness of 52 HRB or more,</li> <li>- casting defects size of not more than 0,4 mm and not more than 10 defects per cm<sup>2</sup>,</li> <li>- a dendrite arm space in combustion chamber of not more than 25 µm,</li> <li>- a double deck water jacket design,</li> <li>- a weight of 14 kg or more but not more than 19 kg,</li> <li>- a length of 506 mm or more but not more than 510 mm,</li> <li>- a height of 282 mm or more but not more than 286 mm and</li> <li>- a width of 143,7 mm or more but not more than 144,3 mm</li> </ul>	Q/100000pieces, 01.07-31.12	New	UNDER EXAMINATION			

8411 99 00		6820127/2024	3357	Turbine ring segments, guide and rotor blades made of nickel-based superalloys, as parts of a stationary gas turbine for power generation or as a mechanical drive	Q/615000kilograms, 01.07-31.12	New	UNDER EXAMINATION			
ex 2309 90 31 ex 2309 90 31 ex 2309 90 96 ex 2309 90 96	51 59 51 59	1995474/2022	6003O	Feed additive, consisting on dry weight basis of: - 68 % or more, but not more than 80 % of L-lysine sulphate, and - not more than 32 % of other components such as carbohydrates and other amino acids, for use in the production of animal feed and/or for use in the production of pharmaceuticals (1)	Q/50000tonnes, 01.01-30.06	Amendment	UNDER EXAMINATION			
ex 2918 22 00	10	1028/2007	6000O	O-acetylsalicylic acid (CAS RN 50-78-2)	Q/120tonnes, 01.01-30.06	Amendment	UNDER EXAMINATION			
ex 2922 41 00	30	2544706/2019	6002O	L-Lysine hydrochloride (CAS RN 657-27-2) or an aqueous solution of L-lysine (CAS RN 56-87-1), containing by weight 50 % or more of L-lysine, for use in the production of animal feed and/or for use in the production of pharmaceuticals (1)	Q/150000tonnes, 01.01-30.06	Amendment	UNDER EXAMINATION			
ex 3811 29 00	80	452962/2013	5008	<b>FR(9.9.2024) amendment:</b> Additives, consisting of 1,3,4-thiadiazolidine-2,5-dithione reaction products with hydrogen peroxide and tert-nonanethiol, containing by weight : - 70 % or more of 2,5-bis(tert-nonyldithio)-[1,3,4]-thiadiazole (CAS RN 89347-09-1), and - 10 % or more of 5-(tert-nonyldithio)- 1,3,4-thiadiazole-2(3H)-thione (CAS RN 97503-12-3), for use in the manufacture of blends of additives for lubricating oils	Q/500tonnes, 01.01-31.12	Amendment	UNDER EXAMINATION			

				<p>---</p> <p><b>Current text:</b></p> <p>Additives containing by weight :</p> <ul style="list-style-type: none"> <li>- 70 % or more of 2,5-bis(tert-nonyldithio)-[1,3,4]-thiadiazole (CAS RN 89347-09-1), and</li> <li>- 10 % or more of 5-(tert-nonyldithio)- 1,3,4-thiadiazole-2(3H)-thione (CAS RN 97503-12-3),</li> </ul> <p>for use in the manufacture of blends of additives for lubricating oils (1)</p>						
ex 8482 99 00	60	4921841/2020	6001	<p>Inner or outer rings made of steel, not hardened or not grinded, outer ring with internal raceway(s), inner ring with external raceway(s), with external diameters of:</p> <ul style="list-style-type: none"> <li>- 14 mm or more but not more than 77 mm for the inner ring,</li> <li>- 26 mm or more but not more than 101 mm for the outer ring,</li> </ul> <p>for use in the manufacture of bearings (1)</p>	Q/2000pieces, 01.01-31.12	Amendment	UNDER EXAMINATION			

CN code	TARIC	Reference Mail	Working Number	Description	Suspensions	New or New request	Measure status	Partner Position Country	Partner Position	Public Comments
2811 22 00		6542070/2024	1030	Silicon dioxide (CAS RN CAS RN 112926-00-8) in powder form with purity by weight of 99 % or more	S	New	UNDER EXAMINATION			

2903 99 80		6374666/2024	1008	4-Bromo-2-fluorobiphenyl (CAS RN 41604-19-7) with a purity by weight of 99 % or more	S	New	UNDER EXAMINATION			
2909 49 80		6675369/2024	3337	2,2'-[oxybis(methylene)]bis[2-ethylpropane-1,3-diol] (CAS RN 23235-61-2) with a purity of 80 % or more by weight	S	New	UNDER EXAMINATION			
2918 30 00		6674744/2024	3336	Ethyl 4-oxopentanoate (CAS RN 539-88-8) with a purity by weight of 98 % or more	S	New	UNDER EXAMINATION			
2920 29 00		6700988/2024	3346	UV absorber, containing: - more than 97 % but not more than 99,8 % by weight of <i>Bis</i> (2,4-dicumylphenyl) pentaerythritol diphosphite (CAS RN 154862-43-8) and - more than 0,2 % but not more than 2 % triisopropanol amine	S	New	UNDER EXAMINATION			
2922 29 00		6559853/2024	3307	<i>N,N</i> -bis(4-methoxybenzyl)amine (CAS RN 17061-62-0) with a purity by weight of 96 % or more	S	New	UNDER EXAMINATION			
2924 19 00		6569422/2024	3313	Pentanoic acid, 5-(dimethylamino)-2-methyl-5-oxo-,methyl ester (CAS RN 1174627-68-9) with a purity by weight of 70 % or more	S	New	UNDER EXAMINATION			
2924 98 59		6532635/2024	1027	Magnesium 2-aminoacetate (IUPAC) with a purity by weight of 100 %	S	New	UNDER EXAMINATION			
2925 29 00		1966069/2024	1511	<b>NL 7.5.24</b> Aqueous solution consisting by weight of: - more than 30 % but not more than 36 % of <i>N,N</i> -dibutyl[bis(diethylamino)]methaniminium chloride (CAS RN 89450-30-6) - not more than 14 % of sodium chloride (CAS RN 7647-14-5) --- <b>FR 2.5.24</b>	S	New	UNDER EXAMINATION			

				<p><i>N,N</i>-Dibutyl[bis(diethylamino)]methaniminium chloride (CAS RN 89450-30-6) with a concentration of more than 30 % but not more than 36 % by weight and sodium chloride (CAS RN 7647-14-5) with a concentration not more than 14 % by weight</p> <p>---</p> <p><b>DK 1.5.24 (supported by IT):</b> Aqueous solution containing by weight 30 % or more, but not more than 36 % of <i>N,N</i>-Dibutyl[bis(diethylamino)]methaniminium chloride (CAS RN 89450-30-6 and by weight not more than 14 % of sodium chloride (CAS RN 7647-14-5)</p> <p>---</p> <p>Dibutyl[<i>bis</i>(diethylamino)]methaniminium chloride (CAS RN 89450-30-6) with a concentration of more than 30 but not more than 36 % by weight and sodium chloride (CAS RN 7647-14-5) with a concentration not more than 14 % by weight</p>						
2932 99 00		6560077/2024	3311	2-butyl-3-(4-hydroxybenzoyl)benzofuran (CAS RN 52490-15-0) with a purity by weight of 99 % or more	S	New	UNDER EXAMINATION			
2933 39 99		6559820/2024	3306	( <i>R</i> )-(-)-3-amino-1-boc-piperidine (CAS RN 188111-79-7) with a purity by weight of 96 % or more	S	New	UNDER EXAMINATION			
2933 39 99		6559904/2024	3308	2,4-dichloro-3-nitropyridine (CAS RN 5975-12-2) with a purity by weight of 99 % or more	S	New	UNDER EXAMINATION			
2933 59 95		6559961/2024	3309	Ruxolitinib phosphate (INN) (CAS RN 1092939-17-7) with a purity by weight of 99 % or more	S	New	UNDER EXAMINATION			
2933 99 80		6501799/2024	1022	<i>N,N</i> -Dimethyl- <i>N</i> -octadecyl-1-octadecanaminium-(sp-4-2)-[29h,31 <i>H</i> -phthalocyanine-2-sulfonato-	S	New	UNDER EXAMINATION			

				n29,n30,n31,n32]cuprate(CAS RN 70750-63-9) with a purity by weight of 90 % or more.						
2933 99 80		6408059/2024	1010	2-(2 <i>H</i> -Benzotriazole-2-yl)-6-(2-phenylpropane-2-yl)-4-(2,4,4-trimethylpentane-2-yl)phenol (CAS RN 73936-91-1) with a purity by weight of 97 % or more	S	New	UNDER EXAMINATION			
2933 99 80		6407956/2024	1009	5 <i>H</i> -Pyrazolo[4,3- <i>c</i> ]pyridine-5-carboxylic acid, 3-amino-2-(4-fluoro-3,5-dimethylphenyl)-2,4,6,7-tetrahydro-4-methyl-, 1,1-dimethylethyl ester, (4 <i>S</i> ) (CAS RN 2212021-59-3) with a purity by weight of 99 % or more	S	New	UNDER EXAMINATION			
2933 99 80		6676141/2024	3340	Poly(oxy-1,2-ethanediyl),alpha-[3-[3-(2 <i>H</i> -benzotriazol-2-yl)-5-(1,1-dimethylethyl)-4-hydroxy-phenyl]-1-oxopropyl]-omega-hydroxy- and poly(oxy-1,2-ethanediyl),alpha-[3-[3-(2 <i>H</i> -benzotriazol-2-yl)-5-(1,1-dimethylethyl)-4-hydroxy- phenyl]-1-oxopropyl]-omega-[3-[3-(2 <i>H</i> -benzotriazol-2-yl)-5-(1,1-dimethylethyl)-4-hydroxyphenyl]-1- oxopropoxy] with a purity by weight of 98 % or more	S	New	UNDER EXAMINATION			
2933 99 80		6700668/2024	3342	2-(2 <i>H</i> -benzotriazol-2-yl)-6-(1-methyl-1-phenylethyl)-4-(1,1,3,3-tetramethylbutyl) phenol (CAS RN 73936-91-1) with a purity by weight of 99 % or more	S	New	UNDER EXAMINATION			
2933 99 80		6469177/2024	1014	6- <i>O</i> - <i>tert</i> -butyl 4a- <i>O</i> -methyl (4a <i>R</i> )-1-(4-fluorophenyl)-4,5,7,8-tetrahydropyrazolo[3,4- <i>g</i> ]isoquinoline-4a,6-dicarboxylate (CAS RN 864972-21-4) with a purity by weight of 95 % or more	S	New	UNDER EXAMINATION			
2934 99 90		6704545/2024	3350	<i>Bis</i> -4 <i>H</i> -3,1-benzoxazin-4-one, 2,2'-(1,4-phenylene)-(CAS RN 18600-59-4)	S	New	UNDER EXAMINATION			
2934 99 90		6704858/2024	3352	2-[4,6- <i>bis</i> ([1,1'-biphenyl]-4-yl)]-1,3,5-triazin-2-yl]-5-[(2-ethylhexyl)oxy]phenol (CAS RN 204583-39-1)	S	New	UNDER EXAMINATION			

3204 13 00		6819860/2024	3355	Mixture of: - 25 % or more but not more than 40 % of Colourant C.I. Basic Blue 3 (CAS RN 33203-82-6) and - 25 % or more but not more than 40 % of C.I. Basic Blue 159 (CAS RN 105953-73-9) and preparations based thereon	S	New	UNDER EXAMINATION			
3204 15 00		6633361/2024	3317	Vat blue 1 solution containing by weight: - 40 % of a mixture (CAS RN 207692-02-2) of Vat Blue 1 reduced K-salt (CAS RN 835912-68-0) and Na-Salt (CAS RN 894-86-0) in the ratio of 3:2; - 0,5 % of Napthalenesulfonic acid, polymer with formaldehyde, sodium salt (CAS RN 9084-06-4); - 2,4 % of Potassium hydroxide (CAS RN 1310-58-3); - 1,6 % of Sodium hydroxide (FKS) (CAS RN 1310-73-2); - 55,5 % of Water (CAS RN 7732-18-5)	S	New	UNDER EXAMINATION			
3204 17 00		6905336/2024	1039	Colourant C.I. Pigment Yellow 110 (CAS RN 5590-18-1) and preparations based thereon with a colourant C.I. Pigment Yellow 110 content of 90 % or more by weight	S	New	UNDER EXAMINATION			
3204 17 00		6905292/2024	1040	Colourant C.I. Pigment Yellow 62 (CAS RN 12286-66-7) and preparations based thereon with a colourant C.I. Pigment Yellow 62 content of 90 or more by weight	S	New	UNDER EXAMINATION			
3204 17 00		6905230/2024	1041	Colourant C.I. Pigment Yellow 17 (CAS RN 4531-49-1) and preparations based thereon with a colourant C.I. Pigment Yellow 17 content of 90 % or more by weight	S	New	UNDER EXAMINATION			
3204 17 00		6532547/2024	1026	Colourant C.I. Pigment Yellow 13 (CAS RN 5102-83-0) and preparations based thereon with a colourant C.I. Pigment Yellow 13 content of 50 % or more by weight	S	New	UNDER EXAMINATION			



3204 17 00		6905393/2024	1038	Colourant C.I. Pigment Yellow 139 (CAS RN 36888-99-0) and preparations based thereon with a colourant C.I. Pigment Yellow 139 content of 90 % or more by weight	S	New	UNDER EXAMINATION			
3204 17 00		6542652/2024	3302	Colourant C.I. Pigment Yellow 174 (CAS n 78952-72-4) and preparations based thereon with a colourant C.I. Pigment Yellow 174 content of 50 % or more by weight.	S	New	UNDER EXAMINATION			
3204 17 00		6905498/2024	1037	Colourant C.I. Pigment Yellow 147 (CAS RN 4118-16-5) and preparations based thereon with a colourant C.I. Pigment Yellow 147 content of 90 % or more by weight	S	New	UNDER EXAMINATION			
3204 17 00		6501729/2024	1021	Colourant C.I. Pigment Red 146 (CAS RN 5280-68-2) and preparations based thereon with a colourant C.I. Pigment Red 146 content of 90 % or more by weight	S	New	UNDER EXAMINATION			
3204 17 00		6501677/2024	1020	Colourant C.I. Pigment Red 264 (CAS RN 88949-33-1) and preparations based thereon with a colourant C.I. Pigment Red 264 content of 90 % or more by weight	S	New	UNDER EXAMINATION			
3204 17 00		6325899/2024	1007	Colourant C.I. Pigment Red 2 (CAS RN 6041-94-7) and preparations based thereon with a colourant C.I. Pigment Red 2 content of 90 % or more by weight	S	New	UNDER EXAMINATION			
3204 17 00		6325804/2024	1006	Colourant C.I. Pigment Yellow 65 (CAS RN 6528-34-3) and preparations based thereon with a colourant C.I. Pigment Yellow 65 content of 90 % or more by weight	S	New	UNDER EXAMINATION			
3204 17 00		6325563/2024	1004	Colourant C.I. Pigment Red 177 (CAS RN 4051-63-2) and preparations based thereon with a colourant C.I. Pigment Red 177 content of 90 % or more by weight	S	New	UNDER EXAMINATION			

3204 17 00		6701125/2024	3348	Colourant C.I. Pigment Blue 29 (CAS RN 57455-37-5) and preparations based thereon with a colourant C.I. Pigment Blue 29 content of 90 % or more by weight	S	New	UNDER EXAMINATION			
3204 17 00		6905728/2024	1033	Colourant C.I. Pigment Yellow 168 (CAS RN 71832-85-4) and preparations based thereon with a colourant C.I. Pigment Yellow 168 content of 90 % or more by weight	S	New	UNDER EXAMINATION			
3204 17 00		6325339/2024	1003	Colourant C.I. Pigment Red 112 (CAS RN 6535-46-2) and preparations based thereon with a colourant C.I. Pigment Red 112 content of 90 % or more by weight	S	New	UNDER EXAMINATION			
3204 17 00		6704383/2024	3349	Colourant C.I. Pigment Yellow 180 (CAS RN 77804-81-0) and preparations based thereon with a colourant C.I. Pigment Yellow 180 content of 90 % or more by weight	S	New	UNDER EXAMINATION			
3204 17 00		6501301/2024	1018	Colourant C.I. Pigment Red 264 (CAS RN 88949-33-1) and preparations based thereon with a colourant C.I. Pigment Red 264 content of 90 % or more by weight	S	New	UNDER EXAMINATION			
3204 17 00		6299757/2024	1000	Colourant C.I. Pigment Red 122 (CAS RN 980-26-7) and preparations based thereon with a colourant C.I. Pigment Red 122 content of 90 % or more by weight	S	New	UNDER EXAMINATION			
3204 17 00		6325279/2024	1002	Colourant C.I. Pigment Yellow 183 (CAS RN 65212-77-3) and preparations based thereon with a colourant C.I. Pigment Yellow 183 content of 90 % or more by weight	S	New	UNDER EXAMINATION			

3204 19 00		6905681/2024	1034	Colourant C.I. Solvent Yellow 114 (CAS RN 17772-51-9) and preparations based thereon with a colourant C.I. Solvent Yellow 114 content of 90 % or more by weight	S	New	UNDER EXAMINATION			
3204 19 00		6905530/2024	1036	Colourant C.I. Solvent Red 52 (CAS RN 81-39-0) and preparations based thereon with a colourant C.I. Solvent Red 52 content of 90 % or more by weight	S	New	UNDER EXAMINATION			
3204 19 00		6905598/2024	1035	Colourant C.I. Solvent Red 135 (CAS RN 71902-17-5) and preparations based thereon with a colourant C.I. Solvent Red 135 content of 90 % or more by weight	S	New	UNDER EXAMINATION			
3206 49 70		6325697/2024	1005	Colourant C.I. Pigment Yellow 164 (CAS RN 68412-38-4) and preparations based thereon with a colourant C.I. Pigment Yellow 164 content of 90 % or more by weight	S	New	UNDER EXAMINATION			
3809 91 00		6559753/2024	3305	Water based antimony pentoxide solution containing by weight 25 % or more but not more than 50 % of diantimony pentoxide (CAS RN 1314-60-9)	S	New	UNDER EXAMINATION			
3812 39 10		6700840/2024	3345	Pentaerythritol tetrakis(3-(3,5-di-tert-butyl-4-hydroxyphenyl)propionate) (CAS RN 6683-19-8)	S	New	UNDER EXAMINATION			
3812 39 90		6700716/2024	3343	Reaction mass of - decanedioic acid, <i>bis</i> (1,2,2,6,6-pentamethyl-4-piperidinyl) ester and - decanedioic acid, (1,2,2,6,6-pentamethyl-4-piperidinyl) methyl ester (CAS RN 1065336-91-5)	S	New	UNDER EXAMINATION			
3812 39 90		6408129/2024	1011	UV stabilizer based on - reaction mass of Poly(oxy-1,2-ethanediyl), .alpha.-[3-[3-(2H-benzotriazol-2-yl)-5-(1,1-dimethylethyl)-4-hydroxyphenyl]-1-oxopropyl]-.omega.-hydroxy- and Poly(oxy-1,2-ethanediyl), .alpha.-[3-[3-(2H-benzotriazol-	S	New	UNDER EXAMINATION			

				<p>2-yl)-5-(1,1-dimethylethyl)-4-hydroxyphenyl]-1-oxopropyl]-.omega.-[3-[3-(2H-benzotriazol-2-yl)-5-(1,1-dimethylethyl)-4-hydroxyphenyl]-1-oxopropoxy] (CAS RN 400-830-7) with a purity by weight of 55 % or more, but not more than 75 %,</p> <ul style="list-style-type: none"> <li>- Bis(1,2,2,6,6-pentamethyl-4-piperidyl)sebacat (CAS RN 41556-26-7) with a purity by weight of 15 % or more, but not more than 35 %, and</li> <li>- Methyl 1,2,2,6,6-pentamethyl-4-piperidylsebacat (CAS RN 82919-37-7) with a purity by weight of 5 % or more, but not more than 15 %</li> </ul>						
3812 39 90		6408250/2024	1012	<p>UV stabilizer based on a</p> <ul style="list-style-type: none"> <li>- reaction mass of branched and linear C7-C9 alkyl 3-[3-(2H-benzotriazol-2-yl)-5-(1,1-dimethylethyl)-4-hydroxyphenyl]propionates (CAS RN 127519-17-9) with a purity by weight of 40 % or more, but not more than 60 %, and a</li> <li>- reaction mass of decanedioic acid, 1,10-bis[2,2,6,6-tetramethyl-1-(octyloxy)-4-piperidiny] ester and decanedioic acid, 1,8-octanediy]bis[oxy(2,2,6,6-tetramethyl-1,4-piperidinediyl)] bis[2,2,6,6-tetramethyl-1-(octyloxy)-4-piperidiny] (CAS RN 29757-67-1) with a purity by weight of 40 % or more, but not more than 60 %</li> </ul>	S	New	UNDER EXAMINATION			
3812 39 90		6701073/2024	3347	<p>Ethyl 4-[[[(methylphenylamino)methylene]amino] benzoate (CAS RN 57834-33-0) with a purity of 99 % or more by weight</p>	S	New	UNDER EXAMINATION			
3812 39 90		6700790/2024	3344	<p>Reaction mass of Octyl-3-[3-tert-butyl-4-hydroxy-5-(5-chloro-2Hbenzotriazole-2-yl) phenyl] propionate (CAS RN 83044-89-7) and 2-Ethylhexyl-3-[3-tert-butyl-4-hydroxy-5-(5-chloro-2H-benzotriazole-2-yl) phenyl] Propionate (CAS RN 83044-90-0)</p>	S	New	UNDER EXAMINATION			

3812 39 90		6675920/2024	3339	Stabiliser containing: - 75 % or more but not more than 95 % by weight of 2-(4,6- <i>bis</i> (2,4-dimethylphenyl)-1,3,5-triazin-2-yl)-5-hydroxyphenol with ((C10-16, rich in C12-13 alkyloxy) methyl) oxyrane (CAS RN 153519-44-9) and - 5 % or more but not more than 25 % by weight of 1-methoxy-2-propanol (CAS RN 107-98-2)	S	New	UNDER EXAMINATION			
3812 39 90		6676427/2024	3341	Light stabilisers containing a mixture of - benzenepropanoic acid, 3-(2 <i>H</i> -benzotriazole-2-yl)-5-(1,1-di-methylethyl)-4-hydroxy-,C7-9 branched and - linear alkyl esters (CAS RN 127519-17-9) in an amount of 92 % or more by weight and 1-methoxy-2-propyl acetate (CAS RN 108-65-6) of more than 2 % but not more than 8 % by weight	S	New	UNDER EXAMINATION			
3815 90 90		6569700/2024	3315	Catalytic preparations for fluid catalytic cracking, in the form of powder, consisting of a mixture of one or more of the following active substances: - calcium carbonate (CAS RN 471-34-1), - copper oxide (CAS RN 1217-38-0), - iron oxide (CAS RN 1309-37-1), - aluminium magnesium vanadium oxide (CAS RN 70621-8-0), - aluminium phosphate (CAS RN 7784-30-7), - cerium oxide (CAS RN 1306-38-3), and one or more of the following inert substances: - magnesium oxide (CAS RN 1309-48-8), - aluminium oxide (CAS RN 1344-28-1), - kaolin (CAS RN 1332-58-7)	S	New	UNDER EXAMINATION			
3824 99 92		6560008/2024	3310	Mixture containing by weight: - 55 % or more but not more than 65 % of (2 <i>S</i> ,3 <i>S</i> ,4 <i>S</i> ,5 <i>R</i> ,6 <i>R</i> )-2-(((2 <i>R</i> ,3 <i>R</i> ,5 <i>S</i> ,6 <i>R</i> )-4-(((2 <i>R</i> ,3 <i>S</i> ,4 <i>S</i> ,5 <i>R</i> ,6 <i>R</i> )-3-acetoxy-4,5-	S	New	UNDER EXAMINATION			

				<i>bis</i> (benzyloxy)-6- ((benzyloxy)methyl)tetrahydro-2 <i>H</i> -pyran-2-yl)oxy)-3,5- <i>bis</i> (benzyloxy)-6-(4-methoxy-4-oxobutoxy)tetrahydro-2 <i>H</i> -pyran-2-yl)methoxy)-6-(((2 <i>S</i> ,3 <i>S</i> ,4 <i>S</i> ,5 <i>R</i> ,6 <i>R</i> )-3-acetoxy-4,5- <i>bis</i> (benzyloxy)-6-((benzyloxy)methyl)tetrahydro-2 <i>H</i> -pyran-2-yl)oxy)methyl)tetrahydro-2 <i>H</i> -pyran-3,4,5-triyl tribenzoate (CAS RN 12334475-58-5), - 35 % or more but not more than and 45 % of tolu-ene (CAS RN 108-88-3)						
3824 99 96		6704901/2024	3353	Preparation containing by weight: - 30 % or more, but not more than 60 % of 3a,4,4a,5,8,8a,9,9a-octahydro-1 <i>H</i> -4,9:5,8-dimethanocyclopenta[b]naphthalene (CAS RN 7158-25-0), - 10 % or more, but not more than 50 % of 3a,4,7,7a-tetrahydro-4,7-methanoindene (CAS RN 77-73-6) and - whether or not 10 % or more, but not more than 40 % of petroleum hydrocarbon resin (CAS RN 68132-00-3)	S	New	UNDER EXAMINATION			
3824 99 96		6542127/2024	1031	Vulcanizing material containing by weight of - 78% or more but not more than 82 % insoluble sulphur (CAS RN 9035-99-8), - 18% or more but not more than 22 % naphthenic oil (CAS RN 64742-52-5), and - less than 0,2 % methyl styrene (CAS RN 98-83-9)	S	New	UNDER EXAMINATION			
3824 99 96		6704973/2024	3354	Preparation containing by weight: - 80 % or more, but not more than 90 % of 3a,4,7,7a-tetrahydro-4,7-methanoindene (CAS RN 77-73-6), and - Whether or not but not more than 10 % of 3a,4,4a,5,8,8a,9,9a-octahydro-1 <i>H</i> -4,9:5,8-dimethanocyclopenta[b]naphthalene (CAS RN 7158-25-0), and - 0,5 % or more, but not more than 3 % of 2,6-di-tert-butyl-p-cresol (CAS RN 128-37-0)	S	New	UNDER EXAMINATION			

3824 99 96		6675420/2024	3338	Butyl methacrylate (CAS RN 97-88-1) of a purity by weight of 99 % or more and methyl methacrylate (CAS RN 80-62-6) of a purity by weight of more than 0,1 % but not more than 0,5 %	S	New	UNDER EXAMINATION			
3824 99 96		6542168/2024	1032	Vulcanizing material containing by weight - 20 % naphthenic oil (CAS RN 64742-52-5), - 80 % insoluble sulfur containing (CAS RN 9035-99-8)	S	New	UNDER EXAMINATION			
3906 90 90		6548275/2024	3304	Acrylonitrile styrene acrylate copolymer in the form of granules containing: - 48 % styrene, - 22 % acrylonitrile, - 29 % butylacrylate, and - 1 % dihydrodicyclopentadienyl acrylate	S	New	UNDER EXAMINATION			
3907 29 20		7015635/2024	1043	Glycerol (CAS RN 31694-55-0), ethoxylated based polyol with a hydroxyl number of 541 or more but not more than 587	S	New	UNDER EXAMINATION			
3907 29 20		6536442/2024	1029	Poly[oxy(methyl-1,2-ethanediyl)], $\alpha$ -hydro- $\omega$ -hydroxy-, ether with $\beta$ -D-fructofuranosyl $\alpha$ -D-glucopyranoside (CAS RN 9049-71-2)	S	New	UNDER EXAMINATION			
3907 29 99		6704740/2024	3351	Polyethylene glycol with an ethylene oxide chain length of not more than 30, having butyl-2-cyano 3-(4-hydroxyphenyl) acrylate end groups (CAS RN 780763-40-8)	S	New	UNDER EXAMINATION			
3911 10 00		6542237/2024	3300	Combination of organic compounds, predominantly 100 % hydrocarbons, obtained as a fraction of the extract from solvent extraction of the residue	S	New	UNDER EXAMINATION			
3911 10 00		6542308/2024	3301	Petroleum resin containing by weight - more than 98 % asphalt (CAS RN 8052-42-4), - less than 2 % Hydrated Amorphous Silica (CAS RN 112926-00-8)	S	New	UNDER EXAMINATION			

3920 30 00		6633644/2024	3323	<p>Biaxially oriented, non-cellular high impact polystyrene (HIPS) foil in rolls whether or not printed with:</p> <ul style="list-style-type: none"> <li>- a thickness of 0,229 mm or more but not more than 0,279 mm,</li> <li>- an opaque with titanium dioxide content of 3 % or more but not more than 3.5 %,</li> <li>- a width of 82,05 mm or more but no more than 83,05 or 107,45 or more but no more than 108,45 mm,</li> <li>- a water mobility of 20 degrees or more but not more than 23 degrees,</li> <li>- a reflectance of 57 % or more,</li> <li>- a waviness of not more than 1 mm out of flatness,</li> <li>- a super hydrophobic coating chemically neutral and non-reactive to other substances, especially to chemical reagents intended for urine diagnostics</li> </ul>	S	New	UNDER EXAMINATION			
3920 62 19		6569498/2024	3314	<p>Three-layer plastic film consisting of a 15 µm fluorinated polymer (FCC) (EVA) layer, a 275 µm polyethylene terephthalate (PET) layer and a 25 µm fluorinated polymer (FCC) layer:</p> <ul style="list-style-type: none"> <li>- with a total thickness of 300-330 µm,</li> <li>- with a tensile strength of <math>\geq 375</math> N/cm in both the longitudinal and transverse directions (ASTM D-882),</li> <li>- with a low thermal shrinkage of <math>\leq 1,0</math> % at 150 °C for 30 minutes,</li> <li>- a low water vapour permeability of <math>\leq 2,5</math> g/m<sup>22</sup>•d, and</li> <li>- with a high breakdown voltage <math>\geq 18</math> kV and a partial discharge voltage <math>\geq 1500</math> VDC (BG/T 123542.2-2009)</li> </ul> <p>to be used as a protective layer on the back of photovoltaic modules, to provide insulation and protection against external influences.</p>	S	New	UNDER EXAMINATION			



3920 99 21		6536343/2024	1028	Polyamide film with a length of 100 µm or more but not more than 200 µm	S	New	UNDER EXAMINATION			
7007 19 80		6663234/2024	3335	<p>A tempered glass in a circular shape with:</p> <ul style="list-style-type: none"> <li>- a light transmittance of 34,2 % or more but not more than 37,8 %,</li> <li>- a diameter of 477,2 mm or more but not more than 477,8 mm,</li> <li>- a thickness of 2,9 mm or more but not more than 3,5 mm,</li> <li>- a weight of 1345 g or more but not more than 1445 g,</li> <li>- 3-zone structure including Euro Deep Gray colour printed zone,</li> </ul> <p>for the cover of door assembly in washing machines (1)</p>	S	New	UNDER EXAMINATION			
7019 80 10		6663116/2024	3333	<p>A vacuum insulation panel consisting of a gas-tight housing surrounding a rigid core devoid of air:</p> <ul style="list-style-type: none"> <li>- with fiberglass or chopped fiberglass filling,</li> <li>- a thickness of 5,6 mm or more but not more than 20,4 mm,</li> <li>- a length of 195 mm or more but not more than 1 835 mm,</li> <li>- a width of 155 mm or more but not more than 545 mm,</li> <li>- a thermal conductivity lower than 2,5 mW/mK,</li> <li>- an internal pressure of 0,1 Pa,</li> <li>- ambient temperature during operation of - 50 °C or more but not more than 70 °C</li> </ul>	S	New	UNDER EXAMINATION			
7606 91 00		6633432/2024	3318	<p>Aluminium cutout of a rounded shape made from non-alloy aluminium AA 1050:</p> <ul style="list-style-type: none"> <li>- laminated with a layer of fleece or hot-melt adhesive,</li> <li>- with a total thickness of 0.9 mm or more, but not more than 1.1 mm,</li> <li>- with an aluminum layer thickness of 0.8 mm or more, but not more than 0.9 mm,</li> </ul>	S	New	UNDER EXAMINATION			

				<ul style="list-style-type: none"> <li>- embossed with a geometric pattern</li> <li>- lacquered and coated with a protective layer</li> </ul>						
8406 81 00		6501845/2024	1023	Industrial steam turbine with: <ul style="list-style-type: none"> <li>- an output of 40 MW or more but not more than 60 MW,</li> <li>- designed for a pressure of not more than 140 bar and a temperature of not more than 540 ° C,</li> <li>- equipped with double seat valves on the live steam side which are operated with a hydraulic servo of not more than 30 bar</li> </ul>	S	New	UNDER EXAMINATION			
8409 99 00		2556095/2024	1512	Die cast aluminium housing for electronic throttle control or exhaust gas recirculation systems: <ul style="list-style-type: none"> <li>- high pressure-casted of EN AC-46000 aluminium,</li> <li>- shot-blasted and machined,</li> <li>- with a height of 100 mm or more but not more than 135 mm,</li> <li>- with a width of 115 mm or more but not more than 150 mm,</li> <li>- with a weight of 210 g or more but not more than 465 g</li> </ul>	S	New	UNDER EXAMINATION			
8412 21 80		6633775/2024	3325	Hydraulic actuators of a kind used in the arms of machines for handling cargo containers: <ul style="list-style-type: none"> <li>- with a weight of 827 kg or more but not more than 935 kg,</li> <li>- with a diameter of 250 mm or more but not more than 330 mm,</li> <li>- with a length of 3480 mm or more but not more than 4115 mm,</li> <li>- with a stroke of 2750 mm or more but not more than 3180 mm,</li> <li>- adapted to work with hydraulic oil at a working pressure of 23 MPa,</li> <li>- whether or not with a maintenance-free bearing without the need for lubrication</li> </ul>	S	New	UNDER EXAMINATION			
8412 21 80		6662606/2024	3326	Hydraulic actuators of a kind used in the machines for handling cargo containers:	S	New	UNDER EXAMINATION			

				<ul style="list-style-type: none"> <li>- with a weight of 45 kg or more but not more than 57 kg,</li> <li>- with a diameter of 119 mm or more but not more than 149 mm,</li> <li>- with a length of 779 mm or more but not more than 1141 mm,</li> <li>- with a stroke of 450 mm or more but not more than 610 mm,</li> <li>- adapted to work with hydraulic oil at a working pressure of 22 MPa or more but not more than 23 Mpa,</li> <li>- whether or not with a maintenance-free bearing without the need for lubrication</li> </ul>						
8414 30 20		6662813/2024	3329	<p>Hermetic refrigeration compressor for R-600a as refrigerant:</p> <ul style="list-style-type: none"> <li>- not charged with refrigerant,</li> <li>- pre-charged with the lubricant oil with oil charge 150 cm<sup>3</sup> or higher, but not higher than 170 cm<sup>3</sup>,</li> <li>- with a brushless DC electric motor (BLDC),</li> <li>- having right side suction connection with inner diameter of 6,44 mm or more, but not more than 6,64 mm and right side discharge connection of inner diameter 4,85 mm or more, but not more than 5,05 mm,</li> <li>- with displacement 9,93 cm<sup>3</sup> or higher, but not higher than 10,13 cm<sup>3</sup>,</li> <li>- running at 1 300 rpm or faster, but not faster than 4 500 rpm,</li> <li>- with a cooling capacity of 80 W or higher, but not higher than 273 W</li> </ul>	S	New	UNDER EXAMINATION			
8414 30 89		7128266/2024	1046	<p>Compressor for motor vehicle air conditioning system:</p> <ul style="list-style-type: none"> <li>- electrical compressor with a power output of more than 0,4 kW but not exceeding 10 kW for use in the manufacture of motor vehicles under Chapter 87</li> </ul> <p>(1)</p>	S	New	UNDER EXAMINATION			

8418 99 90		6662970/2024	3331	<p>An evaporator being a type of heat exchanger, consisting of aluminium pipes with copper ends enclosed with aluminium radiators:</p> <ul style="list-style-type: none"> <li>- measuring 403 x 276 x 70 mm or more, but not more than 464 x 399 x 83 mm,</li> <li>- with a total weight of a set of 236 g or more, but not more than 1 010 g,</li> <li>- with a fixed sensor,</li> <li>- with noise absorber,</li> <li>- with 2, 5 or 7 control and power connection pins terminated with sensor temperature, heater or fuse type of socket</li> </ul> <p>for use in the manufacture of freezers or refrigerators (1)</p>	S	New	UNDER EXAMINATION			
8431 20 00		6662678/2024	3327	<p>Concrete counterweights of a kind used in machines for handling transport containers and forklifts with:</p> <ul style="list-style-type: none"> <li>- a weight of 2 100 kg or more but not more than 13 000 kg,</li> <li>- a height of 30 cm or more but not more than 110 cm,</li> <li>- a length of 160 cm or more but not more than 260 cm,</li> <li>- a width of 195 cm or more but not more than 330 cm,</li> <li>- smoothed edges,</li> <li>- colored pain coated,</li> <li>- whether or not encased steel sheet with a thickness of 5 mm or more</li> </ul>	S	New	UNDER EXAMINATION			
8431 20 00		6662758/2024	3328	<p>Container spreader of a kind used for lifting empty 20' and 40' cargo containers:</p> <ul style="list-style-type: none"> <li>- without an integrated carriage,</li> <li>- suitable for machines with a load capacity of not more than 11 000 kg,</li> <li>- designed to carry one or two containers at a time,</li> <li>- with a top or side mounting,</li> <li>- with an anti-corrosion layer coated,</li> <li>- with a weight of 3 200 kg or more but not more than 4 000 kg</li> </ul>	S	New	UNDER EXAMINATION			

8481 80 59		6501431/2024	1019	<p>Solenoid valve of combustion engine oil pump for regulating the amount of oil in the pump:</p> <ul style="list-style-type: none"> <li>- with cable with length of 550 mm or more but not more than 700 mm with electrical connector</li> <li>- with an operating pressure of not more than 5.5 bar,</li> <li>- with an operating voltage of 9 VDC or more but not more than 16 VDC,</li> <li>- with a valve's base width of 22 mm but not more than 27 mm,</li> <li>- with a valve's length of 55 mm but not more than 110 mm,</li> </ul> <p>for use in the manufacture of engines of motor vehicles (1)</p>	S	New	UNDER EXAMINATION			
8483 10 95		6663039/2024	3332	<p>Assy shaft of DRUM for torque transmission, made of steel (per SM45C for shaft standard and STS430 for ring standard) with:</p> <ul style="list-style-type: none"> <li>- a length of 137,8 mm or more but not more than 138,2 mm</li> <li>- an outer diameter of 23 mm or more but not more than 48,025 mm,</li> <li>- a weight of 1,0245 kg or more but not more than 1,0445 kg,</li> <li>- a hardness of shaft 40 HRC or more but not more than 50 HRC,</li> <li>- a hardness of ring 90 HRB or more, but no more than 120 HRB,</li> <li>- an external 37-teeth spline with major diameter of 41 mm or more but not more than 48 mm</li> </ul>	S	New	UNDER EXAMINATION			
8501 31 00		6633590/2024	3322	<p>Electric brushless direct current motor finished with biocompatible materials such as stainless steel according to specification 17-4 PH or type 303, 316L, 400 with:</p> <ul style="list-style-type: none"> <li>- a three-phase winding,</li> <li>- an output power not exceeding 280 W,</li> <li>- a length with gearhead of 116,1 mm or more but not more than 117,2 mm,</li> </ul>	S	New	UNDER EXAMINATION			

				<ul style="list-style-type: none"> <li>- an external diameter of 13,86 mm or more but no more than 13,92 mm,</li> <li>- a maximum torque of motor with gearhead 246,6 mNm in 25°C</li> <li>- a no-load radial speed of motor with gearhead at 24 V-25°C 9 900 rpm,</li> <li>- a weight of motor with gearhead of 70,5 g or more but not more than 71,5 g,</li> <li>- a resistance to peak temperature of 140°C or more (non-operating),</li> <li>- a maximal air leak between shaft and shaft seals of 15 Pa/s at given 2 Bars of pressure,</li> <li>- 14 functional pins for power and control purpose,</li> <li>- a flexible printed circuit with length of 245 mm but no longer than 255 mm with mounted 8 pin male connector</li> </ul> <p>for use in the manufacture of medical devices with right-left rotation and oscillation function (1)</p>						
8501 31 00		6662876/2024	3330	<p>Brushless DC electric motor, with:</p> <ul style="list-style-type: none"> <li>- a rated voltage DC310V PWM Voltage,</li> <li>- a rated power of 350 W or more but not more than 368 W,</li> <li>- an input power of 500 W or more but not more than 550 W,</li> <li>- output power of 350 W or more but not more than 400 W,</li> <li>- an external diameter without bracket connector and pulley of 143,2 mm or more but not more than 143,8 mm,</li> <li>- a rated speed of 16300 rpm or more but not more than 16500 rpm,</li> <li>- a weight of 2,33 kg or more but not more than 2,40 kg,</li> <li>- a pulley</li> </ul>	S	New	UNDER EXAMINATION			
8501 51 00		6633467/2024	3319	<p>Electric permanent magnet synchronous motor with:</p> <ul style="list-style-type: none"> <li>- an output power of 550 W,</li> <li>- a rotor containing 8 poles generated by permanent magnets made with a composition</li> </ul>	S	New	UNDER EXAMINATION			

				<p>of neodymium-iron-boron (per GB/T 13560 standard) enclosed in polyethylene cover,</p> <ul style="list-style-type: none"> <li>- an outer diameter of motor magnet shaft end with dimension of 10,001 mm or more but no more than 10,007 mm,</li> <li>- terminals located across the radius 32,5 mm and separated by an angle of 21,8°,</li> <li>- a motor housing made of ADC12 or AC46000 aluminium alloy die casting with composition of aluminium-silicon-copper (per JIS H5302 or EN1706 standard),</li> <li>- a back EMF constant (Ke) of 0,03306 V-sec/rad or more but no more than 0,03654 V-sec/rad,</li> <li>- a back EMF harmonics order - 5th of no more than 0,38 % (of fundamental) and 7th of no more than 0,25 % (of fundamental),</li> <li>- a cogging torque of no more than 13 mNm,</li> <li>- a friction torque in ambient temperature of no more than 22 mNm,</li> <li>- a maximum temperature of motor operation not more than 200 °C</li> </ul>						
8501 51 00		6633489/2024	3320	<p>Electric permanent magnet synchronous motor with:</p> <ul style="list-style-type: none"> <li>- an output power of 600 W,</li> <li>- a rotor containing 8 poles generated by permanent magnets made of composition of iron, neodymium, boron and dysprosium enclosed in aluminium cover,</li> <li>- an outer diameter of motor magnet shaft end with dimension of 10,001 mm or more but no more than 10,007 mm,</li> <li>- terminals located across the diameter 59,2 mm and separated by an angle 30,0°,</li> <li>- a housing made of electrogalvanized steel (per JIS G3313 Grade SECE standard) using a deep-drawing stamping process,</li> <li>- a diameter of 88,600 mm or less but no less than 88,546 mm at the motor-system assembly interface,</li> </ul>	S	New	UNDER EXAMINATION			

				<ul style="list-style-type: none"> <li>- a back EMF constant (Ke) of 0,03277 V-sec/rad or more but no more than 0,03623 V-sec/rad,</li> <li>- • a back EMF harmonics order - 5th of no more than 0,35 % (of fundamental) and 7th of no more than 0,30 % (of fundamental),</li> <li>- a cogging torque of no more than 12 mNm,</li> <li>- a friction torque in ambient temperature of no more than 23 mNm,</li> <li>- a maximum temperature of motor operation not more than 200 °C</li> </ul>						
8501 52 20		6633548/2024	3321	<p>Electric permanent magnet synchronous motor with:</p> <ul style="list-style-type: none"> <li>- an output power of 850 W,</li> <li>- a rotor containing 8 poles generated by permanent magnets made with a composition of neodymium-iron-boron (per GB/T 13560 standard) enclosed in polyethylene cover,</li> <li>- an outer diameter of motor magnet shaft end with dimension of 10,001 mm or more but no more than 10,007 mm,</li> <li>- terminals located across the radius 26,2 mm and separated by an angle 30,0°,</li> <li>- a housing made of ADC12 or AC46000 aluminium alloy die casting with composition of aluminium-silicon-copper (per JIS H5302 or EN1706 standard) and anodized coating (per ASTM B580 type E standard),</li> <li>- a back EMF constant (Ke) of 0,04009 V-sec/rad or more but no more than 0,04431 V-sec/rad,</li> <li>- a back EMF harmonics order - 5th of no more than 0,36 % (of fundamental) and 7th of no more than 0,24 % (of fundamental),</li> <li>- a cogging torque of no more than 20 mNm,</li> <li>- a friction torque in ambient temperature of no more than 26,5 mNm,</li> <li>- a maximum temperature of motor operation not more than 200 °C</li> </ul>	S	New	UNDER EXAMINATION			



8503 00 99		2556164/2024	1666	Pressure casted rotor front plate or cover of an electric supercharger: <ul style="list-style-type: none"> <li>- of EN AC-46000 aluminium,</li> <li>- shot-blasted and machined,</li> <li>- with an HBW of 60 or more (2,5/62,5, according to ISO 6506),</li> <li>- with a tensile strength of 240 N/mm<sup>2</sup> or more,</li> <li>- with a height of 22 mm or more but not more than 26 mm,</li> <li>- with a diameter of 128 mm or more but not more than 136 mm,</li> <li>- with a weight of 220 g or more but not more than 250 g</li> </ul>	S	New	UNDER EXAMINATION			
8505 11 10		2544759/2024	1500	Magnetized upper rotor made with steel stack according to standards ASTM A677-07 grade 47F180 or JIS C 2552 Grade 50A310, with: <ul style="list-style-type: none"> <li>- twelve permanent magnets made with neodymium-iron-boron, enclosed in stamped steel stack ring,</li> <li>- a residual induction value 1,21 T or more but not more than 1,32 T. at 25° C,</li> <li>- an inner diameter of 22,735 mm or more but no more than 22,835 mm,</li> <li>- an outer diameter of 30,725 mm or more but no more than 38,025 mm</li> </ul> for use in the manufacture of vehicle's steering system (1)	S	New	UNDER EXAMINATION			
8507 60 00		7128403/2024	1048	Modules used for the assembly of lithium-ion electric accumulators: <ul style="list-style-type: none"> <li>- contains 12 or more cells but not more than 36 cells,</li> <li>- with a nominal capacity of 51 Ah per cell,</li> <li>- with a nominal voltage of 60 V or more, but not more than 120 V,</li> <li>- with a weight of 18 kg or more but not more than 36 kg,</li> <li>- with a width of 100 mm or more but no more than 220 mm,</li> </ul>	S	New	UNDER EXAMINATION			

				<ul style="list-style-type: none"> <li>- with a height of 80 mm or more but no more than 180 mm,</li> <li>- with a length of 700 mm or more but no more than 1 200 mm,</li> </ul> for use in the manufacture of motor vehicles of subheading 8703.60 (1)						
8507 60 00		7128192/2024	1045	Rechargeable lithium-ion battery pack: <ul style="list-style-type: none"> <li>- with a length of 1 050 mm or more but not exceeding 1 070 mm,</li> <li>- with a width of 624 mm or more but not exceeding 636 mm,</li> <li>- with a height of 235 mm or more but not exceeding 255 mm,</li> <li>- with a weight of 210 kg or more but not exceeding 230 kg,</li> <li>- with a nominal capacity of 215 Ah or more but not exceeding 315 Ah,</li> <li>- with power not exceeding 45 kWh,</li> <li>- with a nominal voltage of 100 V or more but not exceeding 175 V,</li> <li>- with a capacity not exceeding 400 Ah</li> </ul>	S	New	UNDER EXAMINATION			
8507 60 00		7128336/2024	1047	Lithium ion battery: <ul style="list-style-type: none"> <li>- contains 48 or more cells but not more than 84 cells</li> <li>- consists of 2 or more modules but not more than 4 modules</li> <li>- with a nominal capacity of 4,08 Ah per cell</li> <li>- with a nominal voltage of 200 V or more, but not more than 426 V</li> <li>- with a weight of 9 kg or more but not more than 48 kg</li> <li>- with a width of 280 mm or more but no more than 360 mm,</li> <li>- with a height of 150 mm or more but no more than 220 mm,</li> <li>- with a length of 600 mm or more but no more than 1 200 mm,</li> </ul> for use in the manufacture of motor vehicles of Chapter 87	S	New	UNDER EXAMINATION			

				(1)						
8537 10 91		6633310/2024	3316	<p>Electronic assembly containing:</p> <ul style="list-style-type: none"> <li>- a microprocessor,</li> <li>- a programmable memory and other electronic components mounted on a printed circuit,</li> <li>- with or without light-emitting diode (LED) or Thin Film Transistor (TFT) or Liquid Crystal Display (LCD technology) indicators for use in the manufacture of products of subheadings 7321 11, 8414 60, 8418 10, 8418 21, 8418 29, 8418 40, 8421 12, 8422 11, 8450 11, 8450 12, 8450 20, 8450 19, 8451 21, 8451 29 and 8516 60</li> </ul> <p>(1)</p>	S	New	UNDER EXAMINATION			
8544 30 00		6633735/2024	3324	<p>The wire harness ensures the board communication with the other components of the car's EPS (Electrical Power Steering) system with:</p> <ul style="list-style-type: none"> <li>- a length of 170 mm or more but not more than 301 mm,</li> <li>- an outer diameter of 4,5 mm or more but not more than 5,20 mm,</li> <li>- an operating temperature of - 40°C or more but not more than 125°C,</li> <li>- exposed wire end with a maximum diameter of 0,8 mm after tinning,</li> <li>- connectors,</li> <li>- a gold or tin plating terminals,</li> <li>- an XL-PE or TPE-E wire insulation material</li> </ul>	S	New	UNDER EXAMINATION			
8544 42 90		6663164/2024	3334	<p>Wire harness with a 26-PIN or 28-PIN wire to board connectors in crimping technology for the transmission of signals and/or electrical power bound by rubber or vinyl or electrical tape or conduit or a weave of extruded string or a combination of thereof for connection of power supply with main printed (circuit) board assembly (PBA) and electrical components of refrigerator or washing machine</p> <p>(1)</p>	S	New	UNDER EXAMINATION			

8708 40 20		6502232/2024	1025	<p>Transmission assembly consisting of:</p> <ul style="list-style-type: none"> <li>- double pinion type planetary gear shifting mechanism,</li> <li>- sport sequential shiftmatic system that does not have lower than 7-speed and not higher than 10-speed</li> <li>- with the dimensions of:</li> <li>- a width of 280 mm or more but no more than 470 mm,</li> <li>- a height of 350 mm or more but no more than 595 mm,</li> <li>- a length of 410 mm or more but no more than 690 mm,</li> <li>- a weight of 70 kg or more but no more than 110 kg,</li> </ul> <p>for use in the manufacture of motor vehicles of Chapter 87 (1)</p>	S	New	UNDER EXAMINATION			
8708 40 50		6502103/2024	1024	<p>Transmission assembly which houses 3 other shafts inside it and offers a rotating switch for shift position, consisting of:</p> <ul style="list-style-type: none"> <li>- cast aluminum body,</li> <li>- differential gear,</li> <li>- 2 electrical machines and gears</li> <li>- with the dimensions of:</li> <li>- a width of 280 mm or more but no more than 470 mm,</li> <li>- a height of 350 mm or more but no more than 595 mm,</li> <li>- alength of 410 mm or more but no more than 690 mm,</li> </ul> <p>for use in the manufacture of motor vehicles of Chapter 87 (1)</p>	S	New	UNDER EXAMINATION			
8708 91 35		6469652/2024	1017	<p>Radiators with corrosion protection, for pressures up to 150 PSI (1034 kPa) with individual replaceable, cooling tubes in brass or copper for use in the production of engine and charge air cooling with a weight of 265 kg or more but not more than 599 kg</p>	S	New	UNDER EXAMINATION			

8708 94 99		2555819/2024	1508	<p>Torsion bar as part of the steering column made of carbon alloy steel (per SAE J1268, grade 5160H of modified chemistry for carbon content of 0,53 or more, but not more than 0,56) with:</p> <ul style="list-style-type: none"> <li>- a shaft torsional stiffness of 2,5 Nm/degree or more but not more than 2,7 Nm/degree,</li> <li>- a length of 107,75 mm or more but no more than 108,25 mm,</li> <li>- an outer diameter of 6,38 mm or more but no more than 6,42 mm,</li> <li>- two external 18-tooth splines on both shaft ends with a major diameter of 6,70 mm or more but</li> <li>- no more than 6,85 mm, as interface to pressing with matting input and output shafts,</li> <li>- entire surface shot peened</li> </ul> <p>for use in the manufacture of vehicle's steering system (1)</p>	S	New	UNDER EXAMINATION			
8708 94 99		2544451/2024	1501	<p>Outer tie rod with a housing made of AISI 4137 (SCM435) steel or EN10083/2- C45R + N steel or JIS G4053-SCM435 low alloy steel, with:</p> <ul style="list-style-type: none"> <li>- a ball stud made of EN 10263/4 – 41CrS4 Q + T steel or AISI 4137 (SCM435) steel or</li> <li>- EN10083/3-42CrMoS4Q + T steel or JIS G4053-SCM435 low alloy steel,</li> <li>- a ball seat made of polyoxymethylene plastic,</li> <li>- an end of the threaded hole to the ball stud center distance of 124 mm or more but no more than 194 mm,</li> <li>- a ball stud diameter of 21,98 mm or more but no more than 22 mm,</li> <li>- a threaded hole depth of 40,5 mm or more but no more than 52 mm with dimensions M14x1,5,</li> <li>- a boot seal,</li> <li>- a boot seal protector and retaining ring,</li> <li>- lubricant,</li> </ul> <p>for use in the in manufacture of vehicle's steering system (1)</p>	S	New	UNDER EXAMINATION			

8708 94 99		2545142/2024	1502	<p>Hub gear made of cold rolled carbon steel (per ASTM A1008), molded into the plastic and pressed on pinion, with:</p> <ul style="list-style-type: none"> <li>- an outer diameter of 81,2 mm or more, but not more than 82,55 mm,</li> <li>- an inner diameter of 25,9 mm or more, but not more than 25,97 mm,</li> <li>- a height of the lower side of inner diameter of 11,63 mm or more, but not more than 12,13 mm,</li> <li>- a height of the upper side of inner diameter of 3,25 mm or more, but not more than 3,5 mm,</li> <li>- an overall height of 11,63 mm or more, but not more than 19,5 mm</li> </ul> <p>for use in the manufacture of vehicle's steering system (1)</p>	S	New	UNDER EXAMINATION			
8708 94 99		2550880/2024	1503	<p>Shaft intermediate steering assembly as part of the steering column with:</p> <ul style="list-style-type: none"> <li>- a torsional stiffness of 25 Nm/degree or more,</li> <li>- a shaft assembly male tubular made of carbon steel welded tube (per GB/T 699 grade 20),</li> <li>- a shaft assembly female tubular made of carbon steel welded tube (per GB/T 699 grade 20),</li> <li>- two spiders universal joint made of chromium alloy steel (per GB/T 5216 grade 20CrMnTiH),</li> <li>- a length in nominal telescope position of 396 mm or more but not more than 467 mm,</li> <li>- a coupling interface on both ends with internal toothing,</li> <li>- two cardan joints on both sides,</li> <li>- a telescope shaft function with a range of 74 mm or more but not more than 115 mm,</li> </ul> <p>for use in the manufacture of vehicle's steering system (1)</p>	S	New	UNDER EXAMINATION			

8708 94 99		2550954/2024	1504	<p>Lower assist shaft as part of the steering column made of carbon steel (per GB/T699 grade 45 or JIS G4051 grade S45C) with:</p> <ul style="list-style-type: none"> <li>- an ultimate torsional strength load of 325 Nm or more and J.A.E.L values of 275 Nm or more,</li> <li>- a length of 66,39 mm or more but not more than 88,64 mm,</li> <li>- an outer diameter of 27,47 mm or more but not more than 28,38 mm,</li> <li>- an inner hole of diameter 6,50 mm or more but not more than 6,58 mm,</li> <li>- an external 26-teeth spline with major diameter 21,18 mm or more but not more than 21,44 mm,</li> <li>- a knurling on a part of outer surface of major diameter 26,0 mm or more but not more than 26,1 mm,</li> <li>- with or without an external 24-tooth spline and with a major diameter 24,75 mm or more but not more than 25 mm,</li> </ul> <p>for use in the manufacture of vehicle's steering syste (1)</p>	S	New	UNDER EXAMINATION			
8708 94 99		2551185/2024	1507	<p>Tubular steering shaft as part of the steering column made of carbon steel welded tube (per EN 10305/2, E235 + C or GB/T699 grade 20) with:</p> <ul style="list-style-type: none"> <li>- an ultimate torsional strength of 300 Nm or more and J.A.E.L values of 275 Nm or more,</li> <li>- a length of 245,48 mm or more but not more than 287,5 mm,</li> <li>- an outer diameter of 23,95 mm or more but not more than 32,25 mm,</li> <li>- an interface for steering wheel connection either in a form of an external 40-tooth spline with major diameter of 17,1 mm or more but not more than 17,5 mm and an internal thread - M12x1,75-6H or in a form of an external hexagon with a short diagonal of 15,05 mm or more but not more than 15,35mm and an internal thread M10x1.5-6H,</li> <li>- an interface either in a form of an internal 10-tooth spline of length of 98 mm or more but</li> </ul>	S	New	UNDER EXAMINATION			

				not more than 160 mm, with minor diameter of 16,1 mm or more but not more than 16,4 or in a form of an internal 48-tooth spline of length of 151 mm or more but not more than 160 mm, with minor diameter of 23,2 mm or more but not more than 23,3 mm, for use in the manufacture of vehicle's steering system (1)						
8708 94 99		2551124/2024	1506	Lower shaft as part of the steering column made of aluminum alloy (per ASTM B221M grade 6105), air quenched and tempered with: <ul style="list-style-type: none"> <li>- an ultimate torsional strength of 260 Nm or more,</li> <li>- a length of 296,7 mm or more but not more than 297,8 mm,</li> <li>- an external 18-tooth spline on all shaft length with major diameter of 28,7 mm or more but not</li> <li>- more than 29 mm,</li> <li>- an 18-tooth internal spline with a minor diameter of 19,7 mm or more but not more than 20 mm,</li> </ul> for use in the manufacture of vehicle's steering system (1)	S	New	UNDER EXAMINATION			
8708 94 99		2551037/2024	1505	Upper assist shaft as part of the steering column made of carbon steel (per GB/T699 grade 45) with: <ul style="list-style-type: none"> <li>- an ultimate torsional strength load of 325 Nm or more and J.A.E.L values of 275 Nm or more,</li> <li>- a length of 165,3 mm or more but not more than 204,2 mm,</li> <li>- an outer diameter of 22,87 mm or more but not more than 22,92 mm,</li> <li>- an internal hole of diameter 6,50 or more but not more than 6,58 mm,</li> <li>- an external spline,</li> </ul> for use in the manufacture of vehicle's steering system (1)	S	New	UNDER EXAMINATION			



9503 00 75		2558847/2024	1509	Miniature engine: <ul style="list-style-type: none"> <li>- consisting of a plastic body,</li> <li>- with shaft length 11 cm or more but not more than 15,5 cm,</li> <li>- allowing the gears to rotate by means of the cables it contains transmitting electric current,</li> </ul> for use in the manufacture of the toys under heading 9503 (1)	S	New	UNDER EXAMINATION			
9503 00 75		2558894/2024	1510	Miniature engine: <ul style="list-style-type: none"> <li>- consisting of a metal body,</li> <li>- allowing the gears to rotate by means of the cables transmitting electric current,</li> </ul> for use in the manufacture of the toys under heading 9503 (1)	S	New	UNDER EXAMINATION			
ex 2841 80 00	20	2656815/2022	5039	<b>AT (13.09.2024):</b> Disodium tungstate (CAS RN 13472-45-2) with a purity by weight of 75 % or more  --- <b>Current description:</b> Disodium tungstate (CAS RN 13472-45-2) with a: <ul style="list-style-type: none"> <li>- purity by weight of 99 % or more,</li> <li>- chlorine content of less than 100 ppm</li> </ul>	S	Amendment	UNDER EXAMINATION			
ex 2850 00 20	80	1997/1/2001	5002	Arsine (CAS RN 7784-42-1) with a purity by volume of 99,999 % or more	S	Amendment	UNDER EXAMINATION			
ex 2907 29 00	85	2514/1/04 3112/1/04	5012	<b>FR(10.09.2024):</b> Phloroglucinol anhydre (CAS RN 108-73-6) or phloroglucinol dihydrate (CAS RN 6099-90-7) with a purity by weight of 95 % or more  --- <b>Current product description:</b> Phloroglucinol whether or not hydrated	S	Amendment	UNDER EXAMINATION			

ex 2909 19 90	30	1914/2/2003	5003	<b>DG ENV:</b> Reaction mass of 1,1,2,3,3,3-hexafluoro-1-methoxy-2-(trifluoromethyl)propane and 1,1,2,2,3,3,4,4,4-nonafluoro-1-methoxybutane  --- Current text: Mixture of isomers of nonafluorobutyl methyl ether or nonafluorobutyl ethyl ether, of a purity by weight of 99 % or more	S	Amendment	UNDER EXAMINATION			
ex 2909 60 90	10	2452/2/04	5057E	Bis( $\alpha,\alpha$ -dimethylbenzyl) peroxide (CAS RN 80-43-3)	S	Amendment	UNDER EXAMINATION			
ex 2914 29 00	40	1687/3/1996	5013	<b>FR(03.09.2024):</b> Bornan-2-one (CAS 76-22-2) with a with a purity by weight of 90 % or more  --- <b>Current product description:</b> Camphor (CAS 76-22-2)	S	Amendment	UNDER EXAMINATION			
ex 2915 39 00	85	288754/2013	5040	<b>FR(13.09.2024):</b> cis 2- tert-butylcyclohexyl acetate (CAS RN 20298-69-5)  --- <b>Current description:</b> 2-tert-Butylcyclohexyl acetate (CAS RN 88-41-5)	S	Amendment	UNDER EXAMINATION			
ex 2918 99 90	70	249933/2009	5014	<b>NL(28.08.2024):</b> Allyl-(3-methylbutoxy)acetate (CAS RN 67634-00-8) with a purity by weight of 95 %  --- <b>Current product description:</b> Allyl-(3-methylbutoxy)acetate (CAS RN 67634-00-8)	S	Amendment	UNDER EXAMINATION			

ex 2920 29 00	50	450636/2013	5020	<b>FR(29.08.2024):</b> Fosetyl-aluminium (CAS RN 39148-24-8) with a purity by weight of 96 % or more  --- <b>Current product description:</b> Fosetyl-aluminium (CAS RN 39148-24-8)	S	Amendment	UNDER EXAMINATION			
ex 2925 11 00	20	462/2/1985	5007	<b>DE(05.07.2024):</b> 1,2-benzisothiazol-3(2H)-one 1,1-dioxide (Saccharin) CAS RN 81-07-2 with a purity by weight of 99 % or more and its derivatives 1,2-benzisothiazol-3(2H)-one 1,1-dioxide (sodium salt) CAS RN 128-44-9 with a purity by weight of 99 % or more  *  <b>AT(12.09.2024):</b> 1,2-benzisothiazol-3(2H)-one 1,1-dioxide, sodium salt (CAS RN 128-44-9) with a purity by weight of 99 % or more  --- <b>Current product description:</b> Saccharin and its sodium salt	S	Amendment	UNDER EXAMINATION			
ex 2926 90 70	50	466/1/1991	5000	<b>DE (27.08.2024):</b> Ethylcyanoacetate (CAS RN 105-56-6) or Methyl cyanoacetate (CAS RN 105-34-0) with a purity by weight of 99,5 % or more  *  <b>FR (04.07.2024):</b> Ethyl cyanoacetate (CAS RN 105-56-6) with a purity by weight of 99,5 % or more  --- <b>Current product description</b> Alkyl or alkoxyalkyl esters of cyanoacetic acid	S	Amendment	UNDER EXAMINATION			

ex 2927 00 00	10	300/3/1991	5700	<b>DE(21.06.2024):</b> 2,2'-Dimethyl-2,2'-azodipropionamidine dihydrochloride (CAS RN 2997-92-4) with a purity by weight of 97 % or more  --- <b>Current description:</b> 2,2'-Dimethyl-2,2'-azodipropionamidine dihydrochloride (CAS RN 2997-92-4)	S	Amendment	UNDER EXAMINATION			
ex 2927 00 00	30	572/6/1999	5021	<b>FR (03.09.2024):</b> 4'-Aminoazobenzene-4-sulphonic acid (CAS RN 104-23-4) with a purity by weight of 90 % or more  --- <b>Current description:</b> 4'-Aminoazobenzene-4-sulphonic acid (CAS RN 104-23-4)	S	Amendment	UNDER EXAMINATION			
ex 2931 49 80	48	1212/2009 1222/4/2003	5016	<b>NL(29.08.2024):</b> Tetrabutylphosphonium acetate (CAS RN 30345-49-4) in the form of an aqueous solution, containing by weight 40 % or more but not more than 50 % of tetrabutylphosphonium acetate  --- <b>Current product description:</b> Tetrabutylphosphonium acetate in the form of an aqueous solution (CAS RN 30345-49-4)	S	Amendment	UNDER EXAMINATION			
ex 2932 20 90	80	889/05	5056	<b>FR(11.09.2024):</b> Gibberellic acid with a minimum purity by weight of 88 % (CAS RN 77-06-5) for use in the manufacture of plant protection products  --- <b>Current description:</b> Gibberellic acid with a minimum purity by weight of 88 % (CAS RN 77-06-5) (1)	S	Amendment	UNDER EXAMINATION			

ex 2933 59 95	15	877/1/2004	5015	<b>NL(28.08.2024):</b> Sitagliptin phosphate monohydrate (INN) (CAS RN 654671-77-9) with a purity by weight of 95 %  --- <b>Current product description:</b> Sitagliptin phosphate monohydrate (CAS RN 654671-77-9)	S	Amendment	UNDER EXAMINATION			
ex 3204 14 00	10	3058487/2014	5006	Colourant C.I. Direct Black 80 (CAS RN 8003-69-8) and preparations based thereon with a colourant C.I. Direct Black 80 content of 90 % or more by weight	S	Amendment	UNDER EXAMINATION			
3301 12 10		497/3/1995	5022	<b>FR (06.09.2024):</b> Essential oil of sweet orange (CAS RN 8028-48-6) or essential oil of sour orange (CAS RN 72968-50-4), not deterpenated  --- <b>Current description:</b> Essential oil of orange, not deterpenated	S	Amendment	UNDER EXAMINATION			
ex 3402 90 10	20	1283/3/1983	5019	<b>NL(29.08.2024):</b> Mixture, containing by weight: - 80 % or more but not more than 90 % of docusate sodium (INN) (CAS RN 577-11-7), and - 10 % or more but not more than 20 % of sodium benzoate (CAS RN 532-32-1)  --- <b>Current product description:</b> Mixture of docusate sodium (INN) and sodium benzoate	S	Amendment	UNDER EXAMINATION			
ex 3811 29 00	25	827274/2014	5023	<b>FR (05.09.2024):</b> Additives consisting of reaction products of C14-18 saturated and C18 unsaturated alcohols esterified with phosphorus pentoxide and salted with C12-14,-tert-alkylamines (CAS RN 1471315-74-	S	Amendment	UNDER EXAMINATION			

				8) for use in the manufacture of blends of additives for lubricating oils or greases  --- <b>Current description:</b> Additives containing at least salts of primary amines and mono- and di-alkylphosphoric acids, for use in the manufacture of lubricating oils or greases (1)						
ex 3811 29 00	35	827293/2014	5024	<b>FR (05.09.2024):</b> Reaction products of fatty acids, C14-C18 (branched and linear) and C18 (unsaturated) with tetraethylenepentamine (linear, branched, cyclic) (CAS RN 68784-17-8), for use in the manufacture of lubricating oils  --- <b>Current description:</b> Additives consisting of an imidazoline based mixture (CAS RN 68784-17-8), for use in the manufacture of lubricating oils (1)	S	Amendment	UNDER EXAMINATION			
ex 3811 29 00	70	452903/2013	5025	<b>FR (05.09.2024):</b> Phosphonic acid, mixed C12-20-alkyl and C14-18-unsaturated alkyl derivatives (CAS 93925-25-8), containing more than 80 % by weight of oleyl, palmityl and stearyl groups, for use in the manufacture of lubricating oils  --- <b>Current description:</b> Additives consisting of dialkylphosphites (in which the alkyl groups contain more than 80 % by weight of oleyl, palmityl and stearyl groups), for use in the manufacture of lubricating oils (1)	S	Amendment	UNDER EXAMINATION			
ex 3812 39 90	20	1301/6/1994	5747	<b>DE(24.06.2024):</b>	S	Amendment	UNDER EXAMINATION			

				<p>Reaction mass of bis[2,2,6,6-tetramethyl-1-(octyloxy)piperidin-4-yl] decanedioate and 1,1'-bis[2,2,6,6-tetramethyl-1-(octyloxy)piperidin-4-yl] 10,10'-{octane-1,8-diylbis[oxy(2,2,6,6-tetramethylpiperidine-1,4-diyl)]} didecanedioate (CAS RN 129757-67-1)</p> <p>---</p> <p><b>Current description:</b> Mixture containing predominantly bis(2,2,6,6-tetramethyl-1-octyloxy-4-piperidyl) sebacate</p>						
ex 3812 39 90	75	1806565/2023	5030	<p><b>DE(27.08.2024):</b> UV stabilizer consisting of a mixture of</p> <ul style="list-style-type: none"> <li>- branched and linear C7 to C9 alkyl esters of [3-(2H-benzotriazol-2-yl)-5-(1,1-dimethylethyl)-4-hydroxy]-1-phenylpropanoic acid (CAS RN 127519-17-9 ) with a share of 85 % or more, and</li> <li>- 2-Methoxy-1-methylethyl acetate (CAS RN 108-65-6) containing not more than 8 % by weight</li> </ul> <p>---</p> <p><b>Current description:</b> UV stabilizer containing a mixture of:</p> <ul style="list-style-type: none"> <li>- branched and linear C7 to C9 alkyl esters of [3-(2H-benzotriazol-2-yl)-5-(1,1-dimethylethyl)-4-hydroxy]-1- phenylpropanoic acid (CAS RN 127519-17-9) in an amount of 95 % by weight or more, and</li> <li>- 2-methoxy-1-methylethyl acetate (CAS RN 108-65-6) in an amount of not more than 5 % by weight</li> </ul>	S	<b>Amendment</b>	UNDER EXAMINATION			
ex 3812 39 90	85	1957248/2022	5031	<p><b>DE(27.08.2025):</b> Light stabilizer, reaction product of stearate methyl ester with 1-(2-hydroxy-2-methylpropoxy)-2,2,6,6-tetramethyl-4-piperidinol (CAS RN 300711-92-6) with a purity of more than 90 % by weight</p>	S	<b>Amendment</b>	UNDER EXAMINATION			

				<p>---</p> <p><b>Current description:</b> Light stabilizer, reaction product of stearic acid methyl ester with 1-(2-hydroxy-2-methylpropoxy)-2,2,6,6-tetramethyl-4-piperidinol (CAS RN 300711-92-6) with a purity of less than 90 % by weight</p>						
ex 3814 00 90	40	3114/5/04	5005	<p><b>DG ENV:</b> Reaction mass of 2-(ethoxydifluoromethyl)-1,1,1,2,3,3,3-heptafluoropropane and 1-ethoxy-1,1,2,2,3,3,4,4,4-nonafluorobutane</p> <p>---</p> <p><b>Current text:</b> Azeotrope mixtures containing isomers of nonafluorobutyl methyl ether and/or nonafluorobutyl ethyl ether</p>	S	Amendment	UNDER EXAMINATION			
ex 3824 99 92	32	230452/2009	5037	<p><b>FR(13.09.2024):</b> Mixture containing by weight:</p> <ul style="list-style-type: none"> <li>- 56 % or more but not more than 85 % of divi-nylbenzene-isomers (CAS 1321-74-0)</li> <li>- 15 % or more but not more than 44 % of ethylvi-nylbenzene-isomers (CAS 28106-30-1)</li> </ul> <p>---</p> <p><b>Current description:</b> Mixture of divinylbenzene-isomers and ethylvinylbenzene-isomers, containing by weight 56 % or more but not more than 85 % of divinylbenzene (CAS RN 1321-74-0)</p>	S	Amendment	UNDER EXAMINATION			
ex 3903 90 90 ex 3911 90 99	60 60	977359/2011	5018	<p>NL(29.08.2024): Copolymer of styrene with maleic anhydride, either partially esterified or completely chemically modified, in flake or powder form</p> <p>---</p> <p><b>Current product description:</b></p>	S	Amendment	UNDER EXAMINATION			



				Copolymer of styrene with maleic anhydride, either partially esterified or completely chemically modified, of an average molecular weight (Mn) of not more than 4500, in flake or powder form						
ex 3911 90 19	15	1889490/2021	5017	<p><b>NL(29.08.2024):</b>  Polyetherimide (CAS RN 61128-46-9, 61128-47-0, 77699-82-2, 96557-46-9, 99904-16-2, 1234673-19-8 or 2803979-49-7)</p> <p>or</p> <p>Polyetherimide of  - 3,3'- or 4,4'-[(isopropylidene)bis(p-phenylenoxy)]diphthalic dianhydride and/or pyromellitic dianhydride, and  - 1,3-benzenediamine and/or 1,4-benzenediamine and/or 4,4'-diamino diphenyl sulfone and/or 4,4'-(9H-fluoren-9-ylidene)bis benzenamine, and/or 4,4'-oxydianiline;  whether or not with phthalic anhydride or amino-terminated polydimethylsiloxane endcaps (CAS RN 61128-46-9, 61128-47-0, 77699-82-2, 96557-46-9, 99904-16-2, 1234673-19-8 or 2803979-49-7)</p> <p>---</p> <p><b>Current product description:</b>  Polyetherimide of 4,4'-[(isopropylidene)bis(p-phenylenoxy)]diphthalic dianhydride and 1,3-benzenediamine or 1,4-benzenediamine (CAS RN 61128-46-9 or CAS RN 61128-47-0)</p>	S	Amendment	UNDER EXAMINATION			
ex 3920 10 89	55	246973/2011	5814	<p>Ethylene vinyl acetate (EVA) film:</p> <ul style="list-style-type: none"> <li>- with a raised relief surface with embossed undulations,</li> <li>- not laminated,</li> <li>- not cross-linked, and</li> <li>- with a thickness of more than 0,3 mm</li> </ul>	S	Amendment	UNDER EXAMINATION			
ex 6804 21 00	30	6660034/2023	5038	<p><b>TR(17.09.2024):</b></p>	S	Amendment	UNDER EXAMINATION			

				<p>Steel wire used for cropping and squaring semiconductors:</p> <ul style="list-style-type: none"> <li>- coated with diamond grains of 5µm or more, but not more than 55µm,</li> <li>- wire diameter 23 µm or more but not exceeding 350 µm,</li> <li>- a breaking strength of 11 N or more, but not exceeding 170</li> </ul> <p>---</p> <p>Steel wire used for cropping and squaring semiconductors:</p> <ul style="list-style-type: none"> <li>- coated with diamond grains of 5 µm or more but not more than 55 µm,</li> <li>- with a wire diameter of 45 µm or more, but not more than 370 µm,</li> <li>- a breaking strength of 11,5 N or more but not more than 200 N</li> </ul>						
<p>ex 8501 31 00</p> <p>ex 8501 32 00</p>	<p>63</p> <p>65</p>	3812069/2015	5050	<p><b>DE (27.08.2024):</b></p> <p>Ready for installation in vehicles or equipment of headings 8432 and 8433, brushless and permanently excited direct current motor with:</p> <ul style="list-style-type: none"> <li>- a specified speed of not more than 6000 rpm,</li> <li>- a minimum output of 400 W, but not more than 1,3 kW (at 12 V), or with a minimum output of 750 W but not more than 1,55 kW (at 36 V),</li> <li>- a flange diameter of 85 mm or more but not more than 200 mm,</li> <li>- a maximum length of 335 mm, measured from the beginning of the shaft to the outer ending,</li> <li>- a housing length of not more than 265 mm, measured from the flange to the outer ending,</li> <li>- a maximum of two-piece (basic housing including electric components and flange with minimum 2 and maximum 11 bore holes) aluminium diecast or sheet steel housing whether or not with a sealing compound (groove with an O-ring and grease),</li> </ul>	S	Amendment	UNDER EXAMINATION			

				<ul style="list-style-type: none"> <li>- a stator with single T-tooth design and single coil windings in 9/6 or 12/8 or 12/10 topology, and</li> <li>- surface magnets,</li> <li>- whether or not with electronic power steering controller,</li> <li>- whether or not with pulley or coupling ,</li> <li>- whether or not with rotor position sensor</li> </ul> <p>---</p> <p><b>Current description:</b>  Ready for installation in vehicles or equipment of headings 8432 and 8433, brushless and permanently excited direct current motor with:</p> <ul style="list-style-type: none"> <li>- a specified speed of not more than 4 100 rpm,</li> <li>- a minimum output of 400 W, but not more than 1,3 kW (at 12 V), or with a minimum output of 750 W but not more than 1,55 kW (at 36 V),</li> <li>- a flange diameter of 85 mm or more but not more than 200 mm,</li> <li>- a maximum length of 335 mm, measured from the beginning of the shaft to the outer ending,</li> <li>- a housing length of not more than 265 mm, measured from the flange to the outer ending,</li> <li>- a maximum of two-piece (basic housing including electric components and flange with minimum 2 and maximum 11 bore holes) aluminium diecast or sheet steel housing whether or not with a sealing compound (groove with an O-ring and grease),</li> <li>- a stator with single T-tooth design and single coil windings in 9/6 or 12/8 topology, and</li> <li>- surface magnets,</li> <li>- whether or not with electronic power steering controller,</li> <li>- whether or not with pulley,</li> <li>- whether or not with rotor position sensor</li> </ul>						
--	--	--	--	--	--	--	--	--	--	--

ex 8501 51 00 ex 8501 52 20	60  60	1952918/2023	5004	<p><b>DE(27.08.2024):</b> Automotive-ready brushless permanently excited magnet synchronous AC-motor with:</p> <ul style="list-style-type: none"> <li>- a specified speed of not more than 7000 rpm,</li> <li>- a power rating of 400 W or more but not more than 1,8 kW (at 12 V),</li> <li>- a flange diameter of 80 mm or more, but not more than 200 mm,</li> <li>- a maximum length of not more than 335 mm, measured from the beginning of the shaft to its outer end,</li> <li>- a housing length of not more than 265 mm, measured from the flange to the outer end,</li> <li>- a steel sheet or die-cast aluminium basic housing consisting of not more than two parts, including electrical components and a flange with two or more but not more than 11 holes, whether or not with a sealing connection (groove with O-ring and protective grease or liquid seal interface),</li> <li>- a stator with single T-tooth design and single coil winding with 9/6 or 12/10 or 12/8 topology and surface magnets</li> <li>- whether or not with electronic power steering controller,</li> <li>- whether or not with pulley or coupling,</li> <li>- whether or not with rotor position sensor</li> </ul> <p>---</p> <p><b>Current text:</b> Automotive-ready brushless permanently excited magnet synchronous AC-motor with</p> <ul style="list-style-type: none"> <li>- a specified speed of not more than 7 000 rpm,</li> <li>- a power rating of 400 W or more but not more than 1,8 kW (at 12 V),</li> <li>- a flange diameter of 80 mm or more, but not more than 200 mm,</li> <li>- a maximum length of not more than 220 mm, measured from the beginning of the shaft to its outer end,</li> </ul>	S	Amendment	UNDER EXAMINATION			
--------------------------------	--------------	--------------	------	---	---	-----------	-------------------	--	--	--

				<ul style="list-style-type: none"> <li>- a housing length of not more than 180 mm, measured from the flange to the outer end,</li> <li>- a steel sheet or die-cast aluminium basic housing consisting of not more than two parts, including electrical components and a flange with two or more but not more than 11 holes, whether or not with a sealing connection (groove with O-ring and protective grease or liquid seal interface),</li> <li>- a stator with single T-tooth design and single coil winding with 12/10 or 12/8 topology and surface magnets</li> </ul>						
ex 8503 00 98	53	6650648/2023	5051	<p><b>PL(11.09.2024):</b> Pressure casted rotor cover of the cooling channel system in the electrical motor:</p> <ul style="list-style-type: none"> <li>- of EN AC-47100-F aluminum,</li> <li>- with a sealing cap of stainless steel,</li> <li>- shot-blasted and machined,</li> <li>- leakproof to the degree of 1 ml per minute or less under 2,75 bar pressure,</li> <li>- with a hardness of 70 HBW or more (2,5/62,5, according to ISO 6506),</li> <li>- with a tensile strength of 190 N/mm<sup>2</sup> or more,</li> <li>- with a height of 42 mm or more, but not more than 64 mm,</li> <li>- with a diameter of 88 mm or more, but not more than 132 mm,</li> <li>- with a weight of 0,3 kg or more but not more than 0,5 kg</li> </ul> <p>---</p> <p><b>Current description:</b> Pressure casted rotor cover of the cooling channel system in the electrical motor:</p> <ul style="list-style-type: none"> <li>- of EN AC-47100-F aluminum,</li> <li>- with a sealing cap of stainless steel,</li> <li>- shot-blasted and machined,</li> <li>- leakproof to the degree of 1 ml per minute or less under 2,75 bar pressure,</li> <li>- with a hardness of 70 HBW or more (2,5/62,5, according to ISO 6506),</li> </ul>	S	Amendment	UNDER EXAMINATION			

				<ul style="list-style-type: none"> <li>- with a tensile strength of 240 N/mm<sup>2</sup> or more,</li> <li>- with a height of 50 mm or more, but not more than 55 mm,</li> <li>- with a diameter of 109 mm or more, but not more than 112 mm,</li> <li>- with a weight of 3,9 kg or more but not more than 4,2 kg</li> </ul>						
ex 8503 00 98	58	6647017/2023	5052	<p><b>PL(11.09.2024):</b> Pressure casted inner housing of a cooling channel system for an electrical motor:</p> <ul style="list-style-type: none"> <li>- of EN AC-47100 aluminum,</li> <li>- shot-blasted and machined,</li> <li>- leakproof to the degree of 3 ml per minute or less under 2,75 bar pressure,</li> <li>- with a hardness of 70 HBW or more (2,5/62,5, according to ISO 6506)</li> <li>- with a tensile strength of 190 N/mm<sup>2</sup> or more,</li> <li>- with a height of 160 mm or more, but not more than 330 mm,</li> <li>- with a diameter of 240 mm or more, but not more than 368 mm,</li> <li>- with a weight of 3 kg or more, but not more than 5,84 kg</li> </ul> <p>---</p> <p><b>Current description:</b> Pressure casted inner housing of a cooling channel system for an electrical motor:</p> <ul style="list-style-type: none"> <li>- of EN AC-47100 aluminum,</li> <li>- shot-blasted and machined,</li> <li>- leakproof to the degree of 3 ml per minute or less under 2,75 bar pressure,</li> <li>- with a hardness of 70 HBW or more (2,5/62,5, according to ISO 6506)</li> <li>- with a tensile strength of 240 N/mm<sup>2</sup> or more,</li> <li>- with a height of 225 mm or more, but not more than 280 mm,</li> </ul>	S	Amendment	UNDER EXAMINATION			

				<ul style="list-style-type: none"> <li>- with a diameter of 300 mm or more, but not more than 310 mm,</li> <li>- with a weight of 3,8 kg or more, but not more than 4,9 kg</li> </ul>						
ex 8503 00 98	63	6647219/2023	5055	<p><b>PL (11.09.2024):</b> Pressure casted outer housing of an electrical motor:</p> <ul style="list-style-type: none"> <li>- of EN AC-47100 aluminum,</li> <li>- with or without overmolded bearing sleeves of martensitic stainless steel and assembled sealing caps of stainless steel,</li> <li>- shot-blasted and machined,</li> <li>- with or without a rotor chamber, leakproof to the degree of 3 ml per minute or less under 2,75 bar pressure,</li> <li>- with a hardness of 70 HBW or more (2,5/62,5, according to ISO 6506)</li> <li>- with a tensile strength of 190 N/mm<sup>2</sup> or more,</li> <li>- with a height of 195 mm or more, but not more than 430 mm,</li> <li>- with a width of 290 mm or more, but not more than 625 mm,</li> <li>- with a length of 270 mm or more, but not more than 535 mm,</li> <li>- with a weight of 5,2 kg or more, but not more than 12,5 kg</li> </ul> <p>---</p> <p><b>Current description:</b> Pressure casted outer housing of an electrical motor:</p> <ul style="list-style-type: none"> <li>- of EN AC-47100 aluminum,</li> <li>- with overmolded bearing sleeves of martensitic stainless steel and assembled sealing caps of stainless steel,</li> <li>- shot-blasted and machined,</li> <li>- a rotor chamber, leakproof to the degree of 3 ml per minute or less under 2,75 bar pressure,</li> <li>- with a hardness of 70 HBW or more (2,5/62,5, according to ISO 6506)</li> </ul>	S	Amendment	UNDER EXAMINATION			

				<ul style="list-style-type: none"> <li>- with a tensile strength of 240 N/mm<sup>2</sup> or more,</li> <li>- with a height of 245 mm or more, but not more than 360 mm,</li> <li>- with a width of 360 mm or more, but not more than 525 mm,</li> <li>- with a length of 345 mm or more, but not more than 450 mm,</li> <li>- with a weight of 6,4 kg or more, but not more than 8,3 kg</li> </ul>						
ex 8507 60 00	26	6609698/2023	5010B	<p><b>IT(27.08.2024):</b> Modules for the assembly of electric accumulators using lithium ferrophosphate technology (LFP) with:</p> <ul style="list-style-type: none"> <li>- a length of 670 mm or more, but not more than 882 mm,</li> <li>- a width of 390 mm or more, but not more than 655 mm,</li> <li>- a height of 110 mm or more, but not more than 137 mm,</li> <li>- a weight of 60 kg or more, but not more than 165 kg, and</li> <li>- a power of 11 300 Wh or more, but not more than 29 360 Wh</li> </ul> <p>---</p> <p><b>Current text:</b> Modules for the assembly of electric accumulators using lithium ferrophosphate technology (LFP) with:</p> <ul style="list-style-type: none"> <li>- a length of 820 mm or more, but not more than 882 mm,</li> <li>- a width of 390 mm or more, but not more than 655 mm,</li> <li>- a height of 110 mm or more, but not more than 137 mm,</li> <li>- a weight of 60 kg or more, but not more than 165 kg, and</li> <li>- a power of 11 300 Wh or more, but not more than 29 360 Wh</li> </ul>	S	Amendment	UNDER EXAMINATION			



ex 8507 60 00	48	4922932/2020	5011B	<p><b>IT(27.08.2024) request for amendment:</b>  Integrated battery system in a metal/plastic case with or without holders, consisting of:</p> <ul style="list-style-type: none"> <li>- a lithium-ion battery with a voltage of 36 V or more but not more than 50,4 V and a nominal energy between 0,3kWh and 0,9 kWh,</li> <li>- Battery Management System,</li> <li>- a power relay,</li> <li>- a cooling system,</li> <li>- one to four connectors,</li> </ul> <p>for use in the manufacture of Mild-hybrid (mHEV) motor vehicles</p> <p>---</p> <p><b>Current text:</b>  Integrated battery system in a metal case with holders, consisting of:</p> <ul style="list-style-type: none"> <li>- a lithium-ion battery with a voltage of 36 V or more but not more than 50,4 V and a nominal energy of 0,6 kWh,</li> <li>- Battery Management System,</li> <li>- a power relay,</li> <li>- a cooling system,</li> <li>- four connectors,</li> </ul> <p>for use in the manufacture of Mild-hybrid (mHEV) motor vehicles</p> <p>(1)</p>	S	Amendment	UNDER EXAMINATION				
---------------	----	--------------	-------	---	---	-----------	-------------------	--	--	--	--

(1) Suspension of duties is subject to end-use customs supervision in accordance with Article 254 of Regulation (EU) No 952/2013.

**DISCLAIMER:** The duty suspension and quota requests on the following list are currently under discussion. The data available on this list may not represent the final state of the discussions within the relevant Commission Working group. Please note that it cannot be guaranteed that the information available exactly reproduces an officially adopted text. Only European Union legislation published in the Official Journal of the European Union is deemed authentic.